



SAFETY DATA SHEET

COMMA - WHITE GREASE AEROSOL

Page: 1

Compilation date: 25-01-2012

Revision No: 13

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: COMMA - WHITE GREASE AEROSOL

Product code: WGR500M

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Grease.

1.3. Details of the supplier of the safety data sheet

Company name: Comma Oil & Chemicals Ltd.

Dering Way

Gravesend

Kent

DA12 2QX

Tel: +44 01474 564311

Fax: +44 01474 333000

Email: sales@commaoil.com

1.4. Emergency telephone number

Emergency tel: +44 01474 564311

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CHIP: F+: R12; N: R51/53; -: R66; -: R67

Most important adverse effects: Extremely flammable. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.

2.2. Label elements

Label elements under CHIP:

Hazard symbols: Extremely flammable.

Dangerous for the environment.



Risk phrases: R12: Extremely flammable.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

Safety phrases: S2: Keep out of the reach of children.

S23: Do not breathe spray.

S26: In case of contact with eyes, rinse immediately with plenty of water and seek

[cont...]

SAFETY DATA SHEET

COMMA - WHITE GREASE AEROSOL

Page: 2

medical advice.

S29: Do not empty into drains.

S46: If swallowed, seek medical advice immediately and show this container or label.

S51: Use only in well-ventilated areas.

Precautionary phrases: Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children.

2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

PBT: This substance is not identified as a PBT substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

PENTANE

EINECS	CAS	CHIP Classification	CLP Classification	Percent
203-692-4	109-66-0	F+: R12; N: R51/53; Xn: R65; -: R66; -: R67	-	30-60%

PROPANE

200-827-9	74-98-6	F+: R12 Substance with a Community workplace exposure limit.	-	10-30%
-----------	---------	---	---	--------

BUTANE

203-448-7	106-97-8	F+: R12 Substance with a Community workplace exposure limit.	-	10-30%
-----------	----------	---	---	--------

ISOBUTANE

200-857-2	75-28-5	F+: R12 Substance with a Community workplace exposure limit.	-	10-30%
-----------	---------	---	---	--------

NAPHTHA (PETROLEUM), HYDROTREATED LIGHT (<0.1% BENZOL CAS NR. 71-43-2)

265-151-9	64742-49-0	F: R11; Xi: R38; N: R51/53; Xn: R65; -: R67	-	10-30%
-----------	------------	---	---	--------

ZINC ALKYL DITHIOPHOSPHATE

272-028-3	6869-42-3	Xi: R38; Xi: R41; N: R51/53	-	<1%
-----------	-----------	-----------------------------	---	-----

Contains: Hazardous ingredients present at or above regulatory disclosure limits.

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so.

[cont...]

SAFETY DATA SHEET

COMMA - WHITE GREASE AEROSOL

Page: 3

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Inhalation: Exposure may cause coughing or wheezing.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Alcohol resistant foam. Water spray. Carbon dioxide. Dry chemical powder.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Extremely flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture. Vapour may travel considerable distance to source of ignition and flash back.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Eliminate all sources of ignition. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Smoking is forbidden. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Ensure lighting and electrical equipment are not a source of ignition.

[cont...]

SAFETY DATA SHEET

COMMA - WHITE GREASE AEROSOL

Page: 4

7.3. Specific end use(s)

Specific end use(s): No special requirement.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

PENTANE

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	1800 mg/m ³	-	-	-

PROPANE

UK	1800 mg/m ³	7200 mg/m ³	-	-
----	------------------------	------------------------	---	---

BUTANE

UK	1450 mg/m ³	1810 mg/m ³	-	-
----	------------------------	------------------------	---	---

ISOBUTANE

UK	2400 mg/m ³	9600 mg/m ³	-	-
----	------------------------	------------------------	---	---

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Respiratory protection not required.

Hand protection: Protective gloves.

Eye protection: Safety glasses.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Aerosol

Colour: White

Odour: Characteristic odour

Solubility in water: Insoluble

Flash point°C: <0

Vapour pressure: 420kPa @ 20 C

Relative density: 0.672 @ 20 C

9.2. Other information

Other information: Not applicable.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

[cont...]

SAFETY DATA SHEET

COMMA - WHITE GREASE AEROSOL

Page: 5

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.
Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Toxicity values: Not applicable.

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Inhalation: Exposure may cause coughing or wheezing.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: Not applicable.

12.2. Persistence and degradability

Persistence and degradability: No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This substance is not identified as a PBT substance.

12.6. Other adverse effects

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal of packaging: Dispose of as normal industrial waste.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

[cont...]

SAFETY DATA SHEET

COMMA - WHITE GREASE AEROSOL

Page: 6

14.1. UN number

UN number: UN1950

14.2. UN proper shipping name

Shipping name: AEROSOLS

14.3. Transport hazard class(es)

Transport class: 2

14.4. Packing group

14.5. Environmental hazards

Environmentally hazardous: Yes

Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D

Transport category: 2

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

Phrases used in s.2 and 3: R11: Highly flammable.

R12: Extremely flammable.

R38: Irritating to skin.

R41: Risk of serious damage to eyes.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65: Harmful: may cause lung damage if swallowed.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.